

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (currently amended) An electric cord comprising a plurality of wires which electrically connect a vibrator and an input terminal to which a drive signal for driving the vibrator is inputted, wherein

the plurality of wires flow the same electric current,
and

the respective wires are electrically insulated from each other.

2. (original) The electric cord according to claim 1, wherein the electric cord is formed by at least one of twisting, weaving, and bundling a plurality of wire rods each of which is formed by at least one of twisting, weaving, and bundling of the plurality of wires.

3. (currently amended) The electric cord according to claim 1, wherein ~~the wire~~ each of the wires is constituted by a core thread and a conductor winded on the surface of the core thread, and the surface of the conductor is covered with an insulator.

4. (currently amended) The electric cord according to claim 1, wherein ~~the wire~~ each of the wires is constituted by a

core thread and a conductor winded on the surface of the core thread, and the surface of each of the wires is covered with an insulator.

5. (original) The electric cord according to claim 3, wherein the conductor is a rectangular conductor having a rectangular section.

6. (original) The electric cord according to claim 4, wherein the conductor is a rectangular conductor having a rectangular section.

7. (original) A loudspeaker using an electric cord, wherein the electric cord is an electric cord according to claim 1, and the electric cord is used as a signal input line for a voice coil.

8. (new) An electric cord comprising a plurality of wires which electrically connect a vibrator and an input terminal to which a drive signal for driving the vibrator is inputted, wherein

each of the wires is constituted by a core thread and a conductor winded on the surface of the core thread, and

the respective wires are electrically insulated from each other.

9. (new) A loudspeaker electric cord, comprising:

plural wire rods, positioned adjacent each other and electrically isolated from each other, forming a single electrical signal pathway,

the plural wire rods formed of plural wires positioned adjacent each other and electrically isolated from each other,
each wire comprising
a center core formed by a plurality of core threads twisted upon each other,
a conductor wound on the center core, and
an insulator covering a surface of the conductor and a surface of the wire.

10. (new) The cord of claim 9, wherein the insulator is enamel.

11. (new) The cord of claim 9, wherein the insulator covers an entire exterior surface of the conductor.

12. (new) The cord of claim 11, wherein a cross-section of the conductor is rectangular.

13. (new) The cord of claim 9, wherein a part of an exterior surface of the conductor directly contacts the center core.

14. (new) The cord of claim 9, wherein the plural wire rods are positioned adjacent each other by one of being twisted, woven, and bundled.

15. (new) The cord of claim 9, wherein the insulator covering a wire of a first of the wire rods directly contacts the insulator covering a wire of a second of the wire rods.

16. (new) The cord of claim 15, further comprising an connection, at one end of the wire rods, for attachment to an input terminal of a frame associated with a voice coil.

17. (new) The cord of claim 9, wherein the insulator is a resin and the conductor has a rectangular cross-section.

18. (new) The cord of claim 9, wherein,
there are three wire rods, positioned adjacent each other and electrically isolated from each other, and

the three wire rods formed are each form of three wires positioned adjacent each other and electrically isolated from each other.